

660

ASEP-TECH® Blow/Fill/Seal
packaging system



Safeguarding Solutions Through Innovative PACKAGING

- High Speed Production
Large Bottle Machine
- Cap Welder Ready
- Stepped-base design for easy
maintenance and changeover
- Servo controlled fill motion
- 100mL to 2000mL-wide range
container production



Typical products produced with ASEP-TECH® Model 660 Blow/Fill/Seal packaging system



weilerengineering.com



660 ASEP-TECH® Blow/Fill/Seal packaging system



Model 660 dimensions

Number of Cavities	Container Size (mL)	Containers/Hour
10	1000	1850
14	500	2750
16	500	3300
16	250	3700
20	100	5000

Hourly output dependent upon container design and product characteristics. Chart above reflects LDPE resin and aqueous solutions. Customization available based on a customer supplied URS.



OPTIONAL ACCESSORIES FOR THE ASEP-TECH® BLOW/FILL/SEAL SYSTEM

- Parison shrouding to assure a Class 10,000 environment in the extrusion/parison cutoff zone
- Particle counter for on-line particulate monitoring in the critical zone
- UPS (Uninterruptible Power Supply)
- Chiller
- Vacuum system
- Resin conveyor/blender/granulator
- Recirculating product pathway
- Filter integrity test system
- DMS (Data Management System)
- Conversion/size format changes to mold tooling
- Cap Welder
- A variety of deflashing technology and mechanisms are available
- Mold temperature control unit

The machine depicted is a typical ASEP-TECH® Model 660 Blow/Fill/Seal machine. Dimensions may vary based on optional equipment. A minimum of 4' (122cm) should be provided on sides and front of machine for operation and service. This machine may be protected by one or more domestic or foreign patents. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.